

Global Standard	LESER Global Standard Paint touch-up and painting repaired valves	LGS 4114
		Page 1/4

Contents

1	Purpose	1
2	Scope	1
3	Disclaimer	1
4	Qualified fitting personnel	1
5	General Information	2
6	Paint touch-up and painting repaired valves	2

1 Purpose

This LESER Global Standard (LGS) provides instructions on painting LESER safety valves. The required work steps and materials are described.

2 Scope

This document must be applied when painting safety valves in agencies and subsidiaries of LESER GmbH & Co. KG.

3 Disclaimer

LESER puts in a great deal of effort into making up-to-date and correct documentation available. Nevertheless, LESER GmbH & Co. KG gives no guarantee that the recommended actions presented here are entirely correct and error free. This document is to be applied exclusively to the specified type. LESER GmbH & Co. KG declines any liability or responsibility for the correctness and completeness of the content.

LESER GmbH & Co. KG reserves the right to change the information contained in this document, which is for the products of LESER GmbH & Co. KG and is intended for LESER subsidiaries, at any time and without prior announcement.

LESER GmbH & Co. KG is available to the users of this document to provide additional information.

4 Qualified fitting personnel

The assembly of LESER safety valves may only be performed by trained or qualified fitters. The qualifications must be obtained through the appropriate training measures.

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		

5 General Information



- Wear safety glasses
- Wear respirator/dust mask

6 Paint touch-up and painting repaired valves

For valves that have to be repainted, the facing and the welded-on component/customer ID plates must be masked off correctly. Any additional plates will only be attached after painting, if welding is not required. Open bonnets must be sealed with protective caps. The same applies to any existing threaded holes. Outside threads must be protected with a suitable protective cap / existing painting socket or with masking tape.



Figure 6-1: Protective cap for open bonnet



Figure 6-2: Flange sticker

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		



Figure 6-3: Component plate sticker



Figure 6-4: Protective cap



Figure 6-5: Component plate sticker



Figure 6-6: Protective cap

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		



Figure 6-7: Masking tape



Figure 6-8: Protective cap



Figure 6-9

The layer thickness of the coat of paint should be ~ 40µm for one coat of paint.

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		