

Global Standard	LESER Global Standard	LGS 4116
	Operating materials and supplies for repaired valves	Page 1/3

Contents

1	Purpose	1
2	Scope	1
3	Disclaimer	1
4	Qualified fitting personnel	2
5	General Information	2
6	Operating materials and supplies	2

1 Purpose

This LESER Global Standard (LGS) provides a list of operating materials that are used during the assembly of LESER safety valves.

2 Scope

This document must be observed by all agencies and subsidiaries of LESER GmbH & Co. KG.

3 Disclaimer

LESER puts in a great deal of effort into making up-to-date and correct documentation available. Nevertheless, LESER GmbH & Co. KG gives no guarantee that the recommended actions presented here are completely correct and error free. This document is to be used exclusively with the specified type. LESER GmbH & Co. KG declines any liability or responsibility for the correctness and completeness of the content.

LESER GmbH & Co. KG reserves the right to change the information contained in this document about the products of LESER GmbH & Co. KG that is intended for the LESER subsidiaries at any time and without prior announcement.

LESER GmbH & Co. KG is available to the users of this document to provide additional information.

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		

4 Qualified fitting personnel

The operating materials/supplies that are used during the installation of LESER safety valves must be used exclusively by trained or qualified fitters. The qualifications must be obtained through the appropriate training measures.

5 General Information



Observe the safety regulations and warnings on the packaging.

6 Operating materials and supplies

Lapping paste - Tetrabor

Grit size 320
 600
 800
 1200

Monocrystalline diamond powder - material number N145

Grit size 1.5 – 3 µm

Assembly grease

Molykotepaste – D Paste
Klübersynth UH1 14-151

Halocarbon oil

Oleic acid - PH. EUR 6.0 material number N-206

Superglue

Delo-Ca
Delo-ML 5449 anaerobic high temperature resistant

Leak detection spray

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		

Global Standard	LESER Global Standard	LGS 4116
	Operating materials and supplies for repaired valves	Page 3/3

Güpoflex for gas & compressed air

Quickleen – universal cleaner

Screw glue – LocTITE 222

protected

disclosure cat.:	II	proofread:	OR	published date:	9/14/11	effect. date:	18.11.201
author:	Nieh	released by:	KUW	replaces:	initial	status:	published
resp. depart.:	PP	date of release:	11/8/11	revision No.:	0		
doc. type:	LGS	change rep. No.:	651A	retention period:	10		